



# A&P Technology

## BIAXIAL BRAIDED SLEEVINGS OFFERING:

- Ease of Layup
- Conformability and Repeatability
- Fiber Continuity Providing Superior Impact Performance and Better Fatigue Performance

## WY22L500R Technical Data Sheet

**SLEEVING:** 2 x 2 Twill

**RAW MATERIAL:** 450 Roving Fiberglass

**SLEEVING DIAMETER:** 5.0" (127 mm)

**BRAID ANGLE:** +/-45°

**BRAID YIELD:** 4.1 ft/lb (2.8 m/kg)

**AREAL WEIGHT:** 904 GSM

**LAYER THICKNESS:** (@50%FV): .028" (.71 mm)

**STANDARD SLEEVING TOLERANCES YIELD**

**TOLERANCE:** +/-10%

**ANGLE TOLERANCE:** +/-3°



# Better With Braid.®

For more information, please visit [www.braider.com](http://www.braider.com) OR contact a sales rep at [sales@braider.com](mailto:sales@braider.com) or 513-688-3200

All technical information and data contained herein is believed accurate and reliable. However, the accuracy and completeness of this information is not guaranteed and is subject to change without notice. A&P Technology shall not be liable for injury, loss or damage whether direct or consequential arising out of use of the data provided herein.